











Mod. X-FLEX **IP68 - 69K**

Flexible LED strip IP68 - IP69K for permanent immersion use specifically for decorative or functional lighting of swimming pools, fountains, SPAs, Saunas, Various urban planning, etc. Available in opal finish (clear for special uses). Suitable for obtaining continuous light without the pinpointing of the led.

COLORS AVAILABLE

- Single color: White (2700°K-6500°K), Red, Green, Blue, Amber, Pink
- CCT, RGB, RGB+W, RGB+WW, Pixel/Dynamics

MECHANICAL DIMENSIONS

Width: 16mm Height: 16 mm

AVAILABLE LENGTHS

- Max 25m with power supply (only on one side)
- Max 50m with power supply (on both sides)

WARNING: Strip Til Flex Water cannot be cut, sectioned or lengthened.

ALL OUR TIL FLEX WATER ARE RESISTANT TO CHLORINE, SALT, LIGHT SOLVENTS AND UV RAYS.























Technical data

| Voltage: | 12 - 24 - 48 Volt DC |
|----------------------------------|--------------------------|
| Power: | 5 - 14 W |
| Class. IP: | IP68 - 69K |
| Body Material: | Xpolimers - EPDM |
| Filling: | Opal polyurethane resin |
| | (transparent on request) |
| High efficiency LED light source | |
| Beam angle: | 100°~120° |
| Dimmable: | Yes |
| Duration | 50 000h |

Duration: 50 000h

Curvature: Vertical

Also for permanent immersion use

-40° ~ +110°

Accessories on request:

- Outer casing INOX
- Clips INOX

Temperature:

- Management Systems



